

SECTION 1: IDENTIFICATION

Product Identifier

Product Name: KEY-TO[®] ALGINATE IMPRESSION MATERIAL

Product Code: 013111-000, 013112-000, 013113-000, 013126-000

Intended Use of the Product Key-To alginate comes in a variety of body and set types designed to produce consistent impressions. Quick mixing for smooth handling and fast cleanup. Withdraws easily from undercuts and bands without tearing or distortion.

Name, Address, and Telephone of the Responsible Party

Company

Water Pik, Inc.
1730 East Prospect Road
Fort Collins, CO 80553-0001
800/525-2020 (8 am- 4pm MST)

Emergency Telephone Number

Emergency number : 800/424-9300 (24 Hr: CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Skin Irrit. 2 H315
Eye Dam. 1 H318
Carc. 1A H350
STOT RE 1 H372
Aquatic Acute 3 H402
Aquatic Chronic 2 H411

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US) : Danger

Hazard Statements (GHS-US) : H315 - Causes skin irritation
H318 - Causes serious eye damage
H350 - May cause cancer
H372 - Causes damage to organs through prolonged or repeated exposure
H402 - Harmful to aquatic life
H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements (GHS-US) : P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P260 - Do not breathe dust, fume
P264 - Wash hands, forearms and exposed areas thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P273 - Avoid release to the environment
P280 - Wear protective clothing, protective gloves, eye protection
P302+P352 - IF ON SKIN: Wash with plenty of soap and water
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - If exposed or concerned: Get medical advice/attention
P310 - Immediately call a POISON CENTER or doctor/physician
P314 - Get medical advice and attention if you feel unwell

KEY-TO[®] ALGINATE IMPRESSION MATERIAL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P321 - Specific treatment (see Section 4)
P332+P313 - If skin irritation occurs: Get medical advice/attention
P362 - Take off contaminated clothing and wash before reuse
P391 - Collect spillage
P405 - Store locked up
P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations

Other Hazards

Hazards Not Contributing to the Classification: Overexposure can cause an allergic reaction, dermatitis, abdominal pain, coughing, sneezing, nasal congestion, respiratory sensitization, silicosis, destruction of lung tissue, death.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Name	Product identifier	% (w/w)	Classification (GHS-US)
Diatomaceous earth	(CAS No) 61790-53-2	40 - 70	Not classified
Calcium sulfate	(CAS No) 7778-18-9	7 - 13	Skin Irrit. 2, H315 Eye Dam. 1, H318
Titanate(2-), hexafluoro-, dipotassium, (OC-6-11)-	(CAS No) 16919-27-0	0.5 - 1, 1 - 5 or 5 - 7	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318
Zinc oxide	(CAS No) 1314-13-2	1 - 5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Silica, cristobalite	(CAS No) 14464-46-1	1 - 5	Carc. 1A, H350 STOT RE 1, H372
Tetrasodium pyrophosphate	(CAS No) 7722-88-5	0.5 - 1.5	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318
Limestone	(CAS No) 1317-65-3	0.1 - 1	Not classified

More than one of the ranges of concentration prescribed by Controlled Products Regulations has been used where necessary, due to varying composition.

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: Remove person to fresh air and keep comfortable for breathing. When symptoms occur: go into open air and ventilate suspected area. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 60 minutes. Immediately call a POISON CENTER or doctor/physician.

Ingestion: Rinse mouth. Do NOT induce vomiting.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes skin irritation. Causes serious eye damage. May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Inhalation: May cause respiratory irritation. May cause cancer by inhalation.

Skin Contact: Causes skin irritation.

Eye Contact: Causes serious eye damage.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Causes damage to organs through prolonged or repeated exposure.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible)

KEY-TO[®] ALGINATE IMPRESSION MATERIAL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions are unlikely to occur under normal circumstances.

Advice for Firefighters

Precautionary Measures Fire: Under fire conditions, hazardous fumes will be present.

Firefighting Instructions: Exercise caution when fighting any chemical fire.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Irritating fumes. Oxides of calcium and sulfur. Cristobalite, a form of crystalline silica, which may cause respiratory illness. The OSHA PEL for crystalline silica is 0.05 mg/m³ (respirable).

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not allow product to spread into the environment. Avoid all contact with skin, eyes, or clothing. Do not breathe dust or fumes. Avoid generating dust.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Contact competent authorities after a spill.

Methods and Material for Containment and Cleaning Up

For Containment: Sweep spilled substance into containers; if appropriate, moisten first to prevent dusting.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Avoid actions that cause dust to become airborne during clean-up such as dry sweeping or using compressed air. Use HEPA vacuum or thoroughly wet with water to clean-up dust. Use PPE described in Section 8.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Do not breathe dust or fumes. Inhalation of fumes may cause metal fume fever.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Avoid creating or spreading dust. Ensure adequate ventilation.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Storage Area: Store locked up.

Specific End Use(s) Key-To alginate comes in a variety of body and set types designed to produce consistent impressions. Quick mixing for smooth handling and fast cleanup. Withdraws easily from undercuts and bands without tearing or distortion.

KEY-TO[®] ALGINATE IMPRESSION MATERIAL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Diatomaceous earth (61790-53-2)		
Mexico	OEL TWA (mg/m ³)	10 mg/m ³
British Columbia	OEL TWA (mg/m ³)	1.5 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³
Ontario	OEL TWA (mg/m ³)	3 mg/m ³ (containing no Asbestos and <1% Crystalline silica)
Québec	VEMP (mg/m ³)	6 mg/m ³ (containing no Asbestos and <1% Crystalline silica)
Saskatchewan	OEL STEL (mg/m ³)	6 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	3 mg/m ³
Calcium sulfate (7778-18-9)		
Mexico	OEL TWA (mg/m ³)	10 mg/m ³
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
British Columbia	OEL TWA (mg/m ³)	10 mg/m ³
Manitoba	OEL TWA (mg/m ³)	10 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m ³)	10 mg/m ³
Nova Scotia	OEL TWA (mg/m ³)	10 mg/m ³
Ontario	OEL TWA (mg/m ³)	10 mg/m ³
Prince Edward Island	OEL TWA (mg/m ³)	10 mg/m ³
Québec	VEMP (mg/m ³)	5 mg/m ³ (containing no Asbestos and <1% Crystalline silica)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³
Silica, cristobalite (14464-46-1)		
Mexico	OEL TWA (mg/m ³)	0.05 mg/m ³
USA ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³
USA IDLH	US IDLH (mg/m ³)	25 mg/m ³
Alberta	OEL TWA (mg/m ³)	0.025 mg/m ³
British Columbia	OEL TWA (mg/m ³)	0.025 mg/m ³
Manitoba	OEL TWA (mg/m ³)	0.025 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	0.05 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m ³)	0.025 mg/m ³
Nova Scotia	OEL TWA (mg/m ³)	0.025 mg/m ³
Nunavut	OEL TWA (mg/m ³)	0.15 mg/m ³ (total mass)
Northwest Territories	OEL TWA (mg/m ³)	0.15 mg/m ³ (total mass)
Ontario	OEL TWA (mg/m ³)	0.05 mg/m ³ (designated substances regulation)
Prince Edward Island	OEL TWA (mg/m ³)	0.025 mg/m ³
Québec	VEMP (mg/m ³)	0.05 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	0.05 mg/m ³
Yukon	OEL TWA (mg/m ³)	150 particle/mL
Zinc oxide (1314-13-2)		
Mexico	OEL TWA (mg/m ³)	10 mg/m ³
Mexico	OEL STEL (mg/m ³)	10 mg/m ³
USA ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³
USA ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³

KEY-TO[®] ALGINATE IMPRESSION MATERIAL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

USA NIOSH	NIOSH REL (STEL) (mg/m ³)	10 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	15 mg/m ³
USA IDLH	US IDLH (mg/m ³)	500 mg/m ³
Alberta	OEL STEL (mg/m ³)	10 mg/m ³
Alberta	OEL TWA (mg/m ³)	2 mg/m ³
British Columbia	OEL STEL (mg/m ³)	10 mg/m ³
British Columbia	OEL TWA (mg/m ³)	2 mg/m ³
Manitoba	OEL STEL (mg/m ³)	10 mg/m ³
Manitoba	OEL TWA (mg/m ³)	2 mg/m ³
New Brunswick	OEL STEL (mg/m ³)	10 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	5 mg/m ³
Newfoundland & Labrador	OEL STEL (mg/m ³)	10 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m ³)	2 mg/m ³
Nova Scotia	OEL STEL (mg/m ³)	10 mg/m ³
Nova Scotia	OEL TWA (mg/m ³)	2 mg/m ³
Nunavut	OEL STEL (mg/m ³)	10 mg/m ³
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³ (total mass)
Northwest Territories	OEL STEL (mg/m ³)	10 mg/m ³
Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³ (total mass)
Ontario	OEL STEL (mg/m ³)	10 mg/m ³
Ontario	OEL TWA (mg/m ³)	2 mg/m ³
Prince Edward Island	OEL STEL (mg/m ³)	10 mg/m ³
Prince Edward Island	OEL TWA (mg/m ³)	2 mg/m ³
Québec	VECD (mg/m ³)	10 mg/m ³
Québec	VEMP (mg/m ³)	5 mg/m ³
Saskatchewan	OEL STEL (mg/m ³)	10 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	2 mg/m ³
Yukon	OEL STEL (mg/m ³)	20 mg/m ³
Yukon	OEL TWA (mg/m ³)	10 mg/m ³
Limestone (1317-65-3)		
Mexico	OEL TWA (mg/m ³)	10 mg/m ³
Mexico	OEL STEL (mg/m ³)	20 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
British Columbia	OEL STEL (mg/m ³)	20 mg/m ³
British Columbia	OEL TWA (mg/m ³)	3 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³ (total mass)
Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³ (total mass)
Québec	VEMP (mg/m ³)	10 mg/m ³ (Limestone, containing no Asbestos and <1% Crystalline silica)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³
Yukon	OEL STEL (mg/m ³)	20 mg/m ³
Yukon	OEL TWA (mg/m ³)	10 mg/m ³
Tetrasodium pyrophosphate (7722-88-5)		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	5 mg/m ³
Nunavut	OEL STEL (mg/m ³)	10 mg/m ³
Nunavut	OEL TWA (mg/m ³)	5 mg/m ³

KEY-TO[®] ALGINATE IMPRESSION MATERIAL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Northwest Territories	OEL STEL (mg/m ³)	10 mg/m ³
Northwest Territories	OEL TWA (mg/m ³)	5 mg/m ³
Ontario	OEL TWA (mg/m ³)	5 mg/m ³
Québec	VEMP (mg/m ³)	5 mg/m ³
Saskatchewan	OEL STEL (mg/m ³)	10 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	5 mg/m ³

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed. Provide adequate ventilation to minimize dust concentrations.

Personal Protective Equipment: Gloves. Protective goggles. Protective clothing. Dust formation: dust mask.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or face shield.

Skin and Body Protection: Wear suitable protective clothing. Wash contaminated clothing before reuse.

Respiratory Protection: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

Environmental Exposure Controls: Do not allow the product to be released into the environment.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: Fine white powder
Odor	: Slight
Odor Threshold	: Not available
pH	: Not available
Relative Evaporation Rate (butylacetate=1)	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Specific Gravity	: 0.32
Solubility	: Not soluble in water
Partition coefficient: n-octanol/water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions are unlikely to occur under normal circumstances.

Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

KEY-TO[®] ALGINATE IMPRESSION MATERIAL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage/Irritation: Causes serious eye damage.

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available

Carcinogenicity: May cause cancer.

Specific Target Organ Toxicity (Repeated Exposure): Causes damage to organs through prolonged or repeated exposure.

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause respiratory irritation. May cause cancer by inhalation.

Symptoms/Injuries After Skin Contact: Causes skin irritation.

Symptoms/Injuries After Eye Contact: Causes serious eye damage.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Causes damage to organs through prolonged or repeated exposure.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Calcium sulfate (7778-18-9)	
LD50 Oral Rat	> 3000 mg/kg
Zinc oxide (1314-13-2)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
ATE US (dust, mist)	5.80 mg/l/4h
Tetrasodium pyrophosphate (7722-88-5)	
LD50 Oral Rat	1624 mg/kg (Species: Sprague-Dawley derived, albino)
Diatomaceous earth (61790-53-2)	
IARC Group	3
Silica, cristobalite (14464-46-1)	
IARC Group	1

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Harmful to aquatic life. Toxic to aquatic life with long lasting effects.

Calcium sulfate (7778-18-9)	
LC50 Fish 1	2980 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC 50 Fish 2	> 1970 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
Zinc oxide (1314-13-2)	
LC50 Fish 1	780 µg/l (Exposure time: 96 h - Species: Pimephales promelas)
NOEC chronic fish	0.026 mg/l (Species: Jordanella floridae)

Persistence and Degradability

KEY-TO[®] ALGINATE IMPRESSION MATERIAL	
Persistence and Degradability	Not established. May cause long-term adverse effects in the environment.

Bioaccumulative Potential

KEY-TO[®] ALGINATE IMPRESSION MATERIAL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

KEY-TO[®] ALGINATE IMPRESSION MATERIAL	
Bioaccumulative Potential	Not established.

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Ecology – Waste Materials: This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCES, SOLID, N.O.S. (Contains Zinc Oxide)
Hazard Class : 9
Identification Number : UN3077
Label Codes : 9
Packing Group : III
Marine Pollutant : Marine pollutant
ERG Number : 171



14.2 In Accordance with IMDG

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Contains Zinc Oxide)
Hazard Class : 9
Identification Number : UN3077
Packing Group : III
Label Codes : 9
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-F
Marine pollutant : Marine pollutant



14.3 In Accordance with IATA

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Contains Zinc Oxide)
Packing Group : III
Identification Number : UN3077
Hazard Class : 9
Label Codes : 9
ERG Code (IATA) : 9L



14.4 In Accordance with TDG

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Contains Zinc Oxide)
Packing Group : III
Hazard Class : 9
Identification Number : UN3077
Label Codes : 9



SECTION 15: REGULATORY INFORMATION


US Federal Regulations

KEY-TO[®] ALGINATE IMPRESSION MATERIAL	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
Diatomaceous earth (61790-53-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Calcium sulfate (7778-18-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Silica, cristobalite (14464-46-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

KEY-TO[®] ALGINATE IMPRESSION MATERIAL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Zinc oxide (1314-13-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Limestone (1317-65-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Tetrasodium pyrophosphate (7722-88-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Titanate(2-), hexafluoro-, dipotassium, (OC-6-11)- (16919-27-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
US State Regulations	
Diatomaceous earth (61790-53-2)	
U.S. - New Jersey - Right to Know Hazardous Substance List	
Calcium sulfate (7778-18-9)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	
Silica, cristobalite (14464-46-1)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	
Zinc oxide (1314-13-2)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	
Limestone (1317-65-3)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	
Tetrasodium pyrophosphate (7722-88-5)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	
Canadian Regulations	
KEY-TO[®] ALGINATE IMPRESSION MATERIAL	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
	
Diatomaceous earth (61790-53-2)	
Listed on Non-Domestic Substances List (NDSL)	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
Calcium sulfate (7778-18-9)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Silica, cristobalite (14464-46-1)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
Listed on the Canadian Ingredient Disclosure List	

KEY-TO[®] ALGINATE IMPRESSION MATERIAL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

IDL Concentration 1 %	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
Zinc oxide (1314-13-2)	
Listed on the Canadian DSL (Domestic Substances List) inventory. Listed on the Canadian Ingredient Disclosure List	
IDL Concentration 1 %	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Limestone (1317-65-3)	
Listed on Non-Domestic Substances List (NDSL)	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
Tetrasodium pyrophosphate (7722-88-5)	
Listed on the Canadian DSL (Domestic Substances List) inventory. Listed on the Canadian Ingredient Disclosure List	
IDL Concentration 1 %	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Titanate(2-), hexafluoro-, dipotassium, (OC-6-11)- (16919-27-0)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date : 11/26/2014
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Carc. 1A	Carcinogenicity Category 1A
Comb. Dust	Combustible Dust
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
Comb. Dust	May form combustible dust concentrations in air
H302	Harmful if swallowed
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

Party Responsible for the Preparation of This Document

Water Pik, Inc.

KEY-TO[®] ALGINATE IMPRESSION MATERIAL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Telephone: 800-525-2020

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS 2