

Safety Data Sheet

Copyright, 2015, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| Document Group: | 30-2587-1 | Version Number: | 1.01 |
|-----------------|-----------|------------------|----------|
| Issue Date: | 04/15/15 | Supercedes Date: | 11/08/11 |

Product identifier

4720 3MTM ESPETM FiltekTM P60 Posterior Syringe Intro Kit with Universal Etchant

ID Number(s):

70-2010-8698-3

Recommended use

Dental Product, Dental restorative system **Restrictions on use** For use by dental professionals only.

Supplier's details

| MANUFACTURER: | 3M |
|---------------|-------------------------|
| DIVISION: | 3M ESPE Dental Products |
| | |

| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
|------------|---|
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

18-9028-4, 08-7419-8, 29-8286-6

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy.

4720 3MTM ESPETM FiltekTM P60 Posterior Syringe Intro Kit with Universal Etchant 04/15/15

In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright,2015,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| Document Group: | 18-9028-4 | Version Number: | 10.00 |
|-----------------|-----------|------------------|----------|
| Issue Date: | 05/14/15 | Supercedes Date: | 08/12/13 |

SECTION 1: Identification

1.1. Product identifier

 $3 M^{\rm tm}$ ESPEtm ADPERtm SCOTCHBOND 1 XT

Product Identification Numbers LE-F100-0114-3, 70-2010-3675-6

1.2. Recommended use and restrictions on use

Recommended use

Dental Product, Adhesive **Restrictions on use** For use only by dental professionals

| 1.3. Supplier's details | |
|-------------------------|---|
| MANUFACTURER: | 3M |
| DIVISION: | 3M ESPE Dental Products |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

1.4. Emergency telephone number 1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Flammable Liquid: Category 2. Serious Eye Damage/Irritation: Category 2B. Skin Sensitizer: Category 1B. Specific Target Organ Toxicity (central nervous system): Category 3.

2.2. Label elements Signal word Danger Symbols

Flame | Exclamation mark |

Pictograms



Hazard Statements Highly flammable liquid and vapor.

Causes eye irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness.

Precautionary Statements

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only in a well-ventilated area. Wear protective gloves and eye/face protection. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Call a POISON CENTER or doctor/physician if you feel unwell.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep cool. Keep container tightly closed.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

Although ethyl alcohol is classified as a central nervous system depressant, exposures associated with this health effect are not expected during normal, intended use of this product.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|---------------|------------|------------------------|
| ETHYL ALCOHOL | 64-17-5 | 25 - 35 Trade Secret * |

| BISPHENOL A DIGLYCIDYL ETHER | 1565-94-2 | 10 - 20 Trade Secret * |
|------------------------------------|------------|------------------------|
| DIMETHACRYLATE (BISGMA) | | |
| SILANE_TREATED SILICA | None | 10 - 20 Trade Secret * |
| 2-HYDROXYETHYL METHACRYLATE (HEMA) | 868-77-9 | 5 - 15 Trade Secret * |
| GLYCEROL 1,3-DIMETHACRYLATE | 1830-78-0 | 5 - 10 Trade Secret * |
| COPOLYMER OF ACRYLIC AND ITACONIC | 25948-33-8 | 5 - 10 Trade Secret * |
| ACIDS | | |
| WATER | 7732-18-5 | < 5 Trade Secret * |
| DIURETHANE DIMETHACRYLATE (UDMA) | 72869-86-4 | < 5 Trade Secret * |
| DIPHENYLIODONIUM | 58109-40-3 | < 1 Trade Secret * |
| HEXAFLUOROPHOSPHATE | | |
| ETHYL 4-DIMETHYL AMINOBENZOATE | 10287-53-3 | < 1 Trade Secret * |
| (EDMAB) | | |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

| Hazardous Decomposition or By-Products | | |
|--|-------------------|--|
| Substance | Condition | |
| Carbon monoxide | During Combustion | |
| Carbon dioxide | During Combustion | |

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|---------------|------------|--------|-------------------------|----------------------------|
| ETHYL ALCOHOL | 64-17-5 | OSHA | TWA:1900 mg/m3(1000 ppm |) |
| ETHYL ALCOHOL | 64-17-5 | ACGIH | STEL:1000 ppm | A3: Confirmed animal |
| | | | | carcin. |

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

AIHA : American Industrial Hygiene Association

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| General Physical Form: | Liquid |
|---|--------------------------------------|
| Specific Physical Form: | Liquid |
| Odor, Color, Grade: | Slight acrylate odor, white to clear |
| Odor threshold | No Data Available |
| рН | No Data Available |
| Melting point | Not Applicable |
| Boiling Point | 78 °C |
| Flash Point | 18.5 °C [Test Method: Closed Cup] |
| Evaporation rate | No Data Available |
| Flammability (solid, gas) | Not Applicable |
| Flammable Limits(LEL) | No Data Available |
| Flammable Limits(UEL) | No Data Available |
| Vapor Pressure | No Data Available |
| Vapor Density | No Data Available |
| Density | 1.075 g/ml |
| Specific Gravity | 1.075 [<i>Ref Std:</i> WATER=1] |
| Solubility in Water | Negligible |
| Solubility- non-water | No Data Available |
| Partition coefficient: n-octanol/ water | Not Applicable |
| Autoignition temperature | 410 °C |
| Decomposition temperature | No Data Available |
| Viscosity | No Data Available |
| Percent volatile | No Data Available |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions Hazardous polymerization will not occur.

10.4. Conditions to avoid Heat Sparks and/or flames

10.5. Incompatible materials None known.

10.6. Hazardous decomposition products Substance None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use: Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and

diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use: Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Additional Information:

This product contains ethanol. Alcoholic beverages and ethanol in alcoholic beverages have been classified by the International Agency for Research on Cancer as carcinogenic to humans. There are also data associating human consumption of alcoholic beverages with developmental toxicity and liver toxicity. Exposure to ethanol during the foreseeable use of this product is not expected to cause cancer, developmental toxicity, or liver toxicity.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

| Acute ' | Foxicity |
|---------|-----------------|
|---------|-----------------|

| Name | Route | Species | Value |
|--|-------------|---------------|---|
| Overall product | Ingestion | | No data available; calculated ATE 2,000 - 5,000 |
| | | | mg/kg |
| Overall product | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| ETHYL ALCOHOL | Dermal | Rabbit | LD50 > 15,800 mg/kg |
| ETHYL ALCOHOL | Inhalation- | Rat | LC50 124.7 mg/l |
| | Vapor (4 | | |
| | hours) | | |
| ETHYL ALCOHOL | Ingestion | Rat | LD50 17,800 mg/kg |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) | Ingestion | | LD50 estimated to be 2,000 - 5,000 mg/kg |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE | Dermal | Professio | LD50 estimated to be 2,000 - 5,000 mg/kg |
| (BISGMA) | | nal | |
| | | judgeme | |
| | | nt | |
| SILANE_TREATED SILICA | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| SILANE_TREATED SILICA | Inhalation- | Rat | LC50 > 0.691 mg/l |
| | Dust/Mist | | |
| | (4 hours) | | |
| SILANE_TREATED SILICA | Ingestion | Rat | LD50 > 5,110 mg/kg |
| 2-HYDROXYETHYL METHACRYLATE (HEMA) | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| 2-HYDROXYETHYL METHACRYLATE (HEMA) | Ingestion | Rat | LD50 5,564 mg/kg |
| GLYCEROL 1,3-DIMETHACRYLATE | Ingestion | similar | LD50 300-2000 mg/kg |
| | | compoun | |
| | _ | ds | |
| COPOLYMER OF ACRYLIC AND ITACONIC ACIDS | Dermal | Professio | LD50 estimated to be > 5,000 mg/kg |
| | | nal | |
| | | judgeme | |
| | · . | nt | 1 5 50 5 000 4 |
| COPOLYMER OF ACRYLIC AND ITACONIC ACIDS | Ingestion | Rat | LD50 > 5,000 mg/kg |
| DIURETHANE DIMETHACRYLATE (UDMA) | Dermal | Professio | LD50 estimated to be > 5,000 mg/kg |
| | | nal | |
| | | judgeme nt | |
| DIURETHANE DIMETHACRYLATE (UDMA) | Ingestion | Rat | LD50 > 5,000 mg/kg |
| DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE | Ingestion | Rat | LD50 32 mg/kg |
| ETHYL 4-DIMETHYL AMINOBENZOATE (EDMAB) | Dermal | Rat | |
| | | | LD50 > 2,000 mg/kg |
| ETHYL 4-DIMETHYL AMINOBENZOATE (EDMAB) | Ingestion | Rat | LD50 > 2,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|------------------|---------------------------|
| ETHYL ALCOHOL | Rabbit | No significant irritation |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) | Not available | Minimal irritation |
| SILANE_TREATED SILICA | Rabbit | No significant irritation |
| 2-HYDROXYETHYL METHACRYLATE (HEMA) | Rabbit | Minimal irritation |
| DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE | Rabbit | No significant irritation |
| ETHYL 4-DIMETHYL AMINOBENZOATE (EDMAB) | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|--|-----------|---------------------------|
| | | |
| ETHYL ALCOHOL | Rabbit | Moderate irritant |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) | Not | Moderate irritant |
| | available | |
| SILANE_TREATED SILICA | Rabbit | No significant irritation |
| 2-HYDROXYETHYL METHACRYLATE (HEMA) | Rabbit | Moderate irritant |
| DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE | Rabbit | Mild irritant |
| ETHYL 4-DIMETHYL AMINOBENZOATE (EDMAB) | Rabbit | Mild irritant |

Skin Sensitization

| Name | Species | Value |
|--|---------|--|
| ETHYL ALCOHOL | Human | Some positive data exist, but the data are not |
| | | sufficient for classification |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) | Guinea | Sensitizing |
| | pig | |
| SILANE_TREATED SILICA | Human | Not sensitizing |
| | and | |
| | animal | |
| 2-HYDROXYETHYL METHACRYLATE (HEMA) | Human | Sensitizing |
| | and | |
| | animal | |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|--|----------|--|
| | | |
| ETHYL ALCOHOL | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| ETHYL ALCOHOL | In vivo | Some positive data exist, but the data are not sufficient for classification |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| SILANE_TREATED SILICA | In Vitro | Not mutagenic |
| 2-HYDROXYETHYL METHACRYLATE (HEMA) | In vivo | Not mutagenic |
| 2-HYDROXYETHYL METHACRYLATE (HEMA) | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE | In Vitro | Some positive data exist, but the data are not sufficient for classification |

Carcinogenicity

| Name | Route | Species | Value |
|-----------------------|------------------|-------------------------------|--|
| ETHYL ALCOHOL | Ingestion | Multiple animal species | Some positive data exist, but the data are not sufficient for classification |
| SILANE_TREATED SILICA | Not Specified | Mouse | Some positive data exist, but the data are not sufficient for classification |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|---|------------|--|---------|-----------------------------|------------------------------------|
| ETHYL ALCOHOL | Inhalation | Not toxic to development | Rat | NOAEL 38 mg/l | during gestation |
| ETHYL ALCOHOL | Ingestion | Some positive developmental data exist, but the data are not sufficient for classification | Rat | NOAEL 5,200 mg/kg/day | premating & during gestation |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) | Ingestion | Not toxic to female reproduction | Mouse | NOAEL 0.8 mg/kg/day | premating & during gestation |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) | Ingestion | Not toxic to male reproduction | Mouse | NOAEL 0.8 mg/kg/day | premating & during gestation |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) | Ingestion | Not toxic to development | Mouse | NOAEL 0.8 mg/kg/day | premating & during gestation |
| SILANE_TREATED SILICA | Ingestion | Not toxic to female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| SILANE_TREATED SILICA | Ingestion | Not toxic to male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| SILANE_TREATED SILICA | Ingestion | Not toxic to development | Rat | NOAEL 1,350 mg/kg/day | during organogenesi s |
| 2-HYDROXYETHYL METHACRYLATE (HEMA) | Ingestion | Not toxic to female reproduction | Rat | NOAEL 1,000 mg/kg/day | premating & during gestation |
| 2-HYDROXYETHYL METHACRYLATE (HEMA) | Ingestion | Not toxic to male reproduction | Rat | NOAEL 1,000 mg/kg/day | 49 days |
| 2-HYDROXYETHYL METHACRYLATE (HEMA) | Ingestion | Not toxic to development | Rat | NOAEL 1,000 mg/kg/day | premating & during gestation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---|------------|--------------------------------------|--|-------------------------------|-------------------------|----------------------|
| ETHYL ALCOHOL | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | LOAEL 2.6 mg/l | 30 minutes |
| ETHYL ALCOHOL | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | LOAEL 9.4 mg/l | not available |
| ETHYL ALCOHOL | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Multiple animal species | NOAEL not available | |
| ETHYL ALCOHOL | Ingestion | kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Dog | NOAEL 3,000 mg/kg | |
| COPOLYMER OF ACRYLIC AND ITACONIC ACIDS | Ingestion | nervous system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 5,000 mg/kg | |
| DIPHENYLIODONIUM HEXAFLUOROPHOSPH ATE | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Not available | Irritation Equivocal | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---------------|------------|--|--|---------|-------------------|----------------------|
| ETHYL ALCOHOL | Inhalation | liver | Some positive data exist, but the data are not sufficient for classification | Rabbit | LOAEL 124 mg/l | 365 days |
| ETHYL ALCOHOL | Inhalation | hematopoietic system immune system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 25 mg/l | 14 days |

| ETHYL ALCOHOL | Ingestion | liver | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 8,000 mg/kg/day | 4 months |
|---|------------|--|--|-------|-----------------------------|------------------------------------|
| ETHYL ALCOHOL | Ingestion | kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Dog | NOAEL 3,000 mg/kg/day | 7 days |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) | Ingestion | endocrine system liver nervous system kidney and/or bladder | All data are negative | Mouse | NOAEL 0.8 mg/kg/day | premating & during gestation |
| SILANE_TREATED SILICA | Inhalation | respiratory system silicosis | All data are negative | Human | NOAEL Not available | occupational exposure |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 3 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| Document Group: | 18-9028-4 | Version Number: | 10.00 |
|-----------------|-----------|------------------|----------|
| Issue Date: | 05/14/15 | Supercedes Date: | 08/12/13 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright,2015,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| Document Group: | 29-8286-6 | Version Number: | 2.00 |
|-----------------|-----------|------------------|----------|
| Issue Date: | 02/11/15 | Supercedes Date: | 06/06/12 |

SECTION 1: Identification

1.1. Product identifier

3MTM ESPETM ScotchbondTM Universal Etchant

Product Identification Numbers LE-F100-1014-5, LE-F100-1040-4, 70-2011-3906-3, 70-2011-4006-1, 70-2011-4007-9

1.2. Recommended use and restrictions on use

Recommended use Dental Product, Etching gel Restrictions on use For use only by dental professionals

| 1.3. Supplier's details | |
|-------------------------|---|
| MANUFACTURER: | 3M |
| DIVISION: | 3M ESPE Dental Products |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

1.4. Emergency telephone number 1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Corrosive to metal: Category 1. Serious Eye Damage/Irritation: Category 1. Skin Corrosion/Irritation: Category 1.

2.2. Label elements Signal word Danger

Symbols

Corrosion |

Pictograms



Hazard Statements May be corrosive to metals.

Causes serious eye damage. Causes severe skin burns and eye damage.

Precautionary Statements

Prevention:

Keep only in original container. Do not breathe dust/fume/gas/mist/vapors/spray. Wear protective gloves, protective clothing, and eye/face protection. Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Absorb spillage to prevent material damage.

Storage:

Store in a corrosive resistant container with a resistant inner liner.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

May cause chemical gastrointestinal burns.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|------------------------------------|-------------|------------------------|
| WATER | 7732-18-5 | 50 - 65 Trade Secret * |
| PHOSPHORIC ACID | 7664-38-2 | 30 - 40 Trade Secret * |
| SYNTHETIC AMORPHOUS SILICA, FUMED, | 112945-52-5 | 5 - 10 Trade Secret * |
| CRYSTALLINE FREE | | |
| POLYETHYLENE GLYCOL | 25322-68-3 | 1 - 5 Trade Secret * |
| ALUMINUM OXIDE | 1344-28-1 | < 2 Trade Secret * |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eve Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

| <u>Substance</u> | | | | | |
|------------------|--|--|--|--|--|
| Carbon monoxide | | | | | |
| Carbon dioxide | | | | | |

Condition During Combustion During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Collect as much of the spilled material as possible. Place in a metal container approved for use in transportation by appropriate authorities. The container must be lined with polyethylene plastic or contain a plastic drum liner made of polyethylene. Clean up residue with water. Cover, but do not seal for 48 hours. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid prolonged or repeated skin contact. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. Do not get in eyes.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Keep only in original container. Store in a corrosive resistant container with a resistant inner liner. Store away from strong bases.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|---------------------|------------|--------|------------------------|---------------------|
| ALUMINUM OXIDE | 1344-28-1 | CMRG | TWA:1 fiber/cc | |
| ALUMINUM OXIDE | 1344-28-1 | OSHA | TWA(as total dust):15 | |
| | | | mg/m3;TWA(respirable | |
| | | | fraction):5 mg/m3 | |
| POLYETHYLENE GLYCOL | 25322-68-3 | AIHA | TWA(as particulate):10 | |
| | | | mg/m3 | |
| PHOSPHORIC ACID | 7664-38-2 | ACGIH | TWA:1 mg/m3;STEL:3 | |
| | | | mg/m3 | |
| PHOSPHORIC ACID | 7664-38-2 | OSHA | TWA:1 mg/m3 | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

| 9.1. | Inform | ation | on | basic | physical | and | chemical | properties | |
|------|--------|-------|----|-------|----------|-----|----------|------------|--|
| | | | | | | | | | |

| General Physical Form: | Liquid |
|---|--|
| Specific Physical Form: C | Gel |
| Odor, Color, Grade: S | Slight characteristic odor, Blue |
| Odor threshold | No Data Available |
| pH < | < 1 |
| Melting point N | Not Applicable |
| Boiling Point N | No Data Available |
| Flash Point > | > 100 °C [<i>Test Method:</i> Closed Cup] |
| Evaporation rate N | No Data Available |
| Flammability (solid, gas) | Not Applicable |
| Flammable Limits(LEL) | No Data Available |
| Flammable Limits(UEL) | No Data Available |
| Vapor Pressure N | No Data Available |
| Vapor Density N | No Data Available |
| Density 1 | 1.1 g/ml - 1.2 g/ml |
| Specific Gravity 1 | 1.1 - 1.2 [<i>Ref Std:</i> WATER=1] |
| Solubility in Water C | Complete |
| Solubility- non-water N | No Data Available |
| Partition coefficient: n-octanol/ water N | No Data Available |
| Autoignition temperature N | No Data Available |
| Decomposition temperature <i>N</i> | No Data Available |
| Viscosity N | No Data Available |
| Volatile Organic Compounds N | No Data Available |
| Percent volatile N | No Data Available |
| VOC Less H2O & Exempt Solvents | No Data Available |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability Stable.

10.3. Possibility of hazardous reactions Hazardous polymerization will not occur.

10.4. Conditions to avoid Heat

10.5. Incompatible materials Strong bases

10.6. Hazardous decomposition products

<u>Substance</u> None known. **Condition**

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|------------------------------------|-------------|---------|---|
| Overall product | Dermal | | No data available; calculated ATE > 5,000 mg/kg |
| Overall product | Ingestion | | No data available; calculated ATE 2,000 - 5,000 |
| | | | mg/kg |
| PHOSPHORIC ACID | Dermal | Rabbit | LD50 2,740 mg/kg |
| PHOSPHORIC ACID | Ingestion | Rat | LD50 1,530 mg/kg |
| SYNTHETIC AMORPHOUS SILICA, FUMED, | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| CRYSTALLINE FREE | | | |
| SYNTHETIC AMORPHOUS SILICA, FUMED, | Inhalation- | Rat | LC50 > 0.691 mg/l |
| CRYSTALLINE FREE | Dust/Mist | | |
| | (4 hours) | | |
| SYNTHETIC AMORPHOUS SILICA, FUMED, | Ingestion | Rat | LD50 > 5,110 mg/kg |
| CRYSTALLINE FREE | | | |
| POLYETHYLENE GLYCOL | Dermal | Rabbit | LD50 > 20,000 mg/kg |
| POLYETHYLENE GLYCOL | Ingestion | Rat | LD50 32,770 mg/kg |
| ALUMINUM OXIDE | Dermal | | LD50 estimated to be $> 5,000 \text{ mg/kg}$ |

3MTM ESPETM ScotchbondTM Universal Etchant 02/11/15

| ALUMINUM OXIDE | Inhalation- Dust/Mist (4 hours) | Rat | LC50 > 2.3 mg/l | |
|----------------|---------------------------------------|-----|--------------------|--|
| ALUMINUM OXIDE | Ingestion | Rat | LD50 > 5,000 mg/kg | |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---|---------|---------------------------|
| | | |
| PHOSPHORIC ACID | Rabbit | Corrosive |
| SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE | Rabbit | No significant irritation |
| POLYETHYLENE GLYCOL | Rabbit | Minimal irritation |
| ALUMINUM OXIDE | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|---|--------------------------------|---------------------------|
| PHOSPHORIC ACID | official classifica tion | Corrosive |
| SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE | Rabbit | No significant irritation |
| POLYETHYLENE GLYCOL | Rabbit | Mild irritant |
| ALUMINUM OXIDE | Rabbit | No significant irritation |

Skin Sensitization

| Name | Species | Value |
|---|---------|-----------------|
| PHOSPHORIC ACID | Human | Not sensitizing |
| SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE | Human | Not sensitizing |
| | and | |
| | animal | |
| POLYETHYLENE GLYCOL | Guinea | Not sensitizing |
| | pig | |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|---|----------|---------------|
| | | |
| PHOSPHORIC ACID | In Vitro | Not mutagenic |
| SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE | In Vitro | Not mutagenic |
| POLYETHYLENE GLYCOL | In Vitro | Not mutagenic |
| POLYETHYLENE GLYCOL | In vivo | Not mutagenic |
| ALUMINUM OXIDE | In Vitro | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|--|------------|---------|--|
| SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE | Not | Mouse | Some positive data exist, but the data are not |
| FREE | Specified | | sufficient for classification |
| POLYETHYLENE GLYCOL | Ingestion | Rat | Not carcinogenic |
| ALUMINUM OXIDE | Inhalation | Rat | Not carcinogenic |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure |
|-----------------|-----------|----------------------------------|---------|-------------|--------------|
| | | | | | Duration |
| PHOSPHORIC ACID | Ingestion | Not toxic to female reproduction | Rat | NOAEL 750 | 2 generation |
| | - | _ | | mg/kg/day | - |
| PHOSPHORIC ACID | Ingestion | Not toxic to male reproduction | Rat | NOAEL 750 | 2 generation |
| | - | | | mg/kg/day | - |
| PHOSPHORIC ACID | Ingestion | Not toxic to development | Rat | NOAEL 750 | 2 generation |
| | - | _ | | mg/kg/day | _ |

3MTM ESPETM ScotchbondTM Universal Etchant 02/11/15

| SYNTHETIC AMORPHOUS SILICA, | Ingestion | Not toxic to female reproduction | Rat | NOAEL 509 | 1 generation |
|-----------------------------|-----------|---|-------|--------------|--------------|
| FUMED, CRYSTALLINE FREE | | | | mg/kg/day | |
| SYNTHETIC AMORPHOUS SILICA, | Ingestion | Not toxic to male reproduction | Rat | NOAEL 497 | 1 generation |
| FUMED, CRYSTALLINE FREE | | | | mg/kg/day | |
| SYNTHETIC AMORPHOUS SILICA, | Ingestion | Not toxic to development | Rat | NOAEL | during |
| FUMED, CRYSTALLINE FREE | | | | 1,350 | organogenesi |
| | | | | mg/kg/day | S |
| POLYETHYLENE GLYCOL | Ingestion | Not toxic to female reproduction | Rat | NOAEL | during |
| | | | | 1,125 | gestation |
| | | | | mg/kg/day | |
| POLYETHYLENE GLYCOL | Ingestion | Not toxic to male reproduction | Rat | NOAEL 5699 | 5 days |
| | | | | +/- 1341 | |
| | | | | mg/kg/day | |
| POLYETHYLENE GLYCOL | Not | Some positive | | NOEL N/A | |
| | Specified | reproductive/developmental data exist, | | | |
| | | but the data are not sufficient for | | | |
| | | classification | | | |
| POLYETHYLENE GLYCOL | Ingestion | Some positive developmental data exist, | Mouse | NOAEL 562 | during |
| | | but the data are not sufficient for | | mg/animal/da | gestation |
| | | classification | | y | - |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|------------------------|------------|------------------------|--|---------|------------------------|--------------------------|
| PHOSPHORIC ACID | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | occupational exposure |
| POLYETHYLENE GLYCOL | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 1.008 mg/l | 2 weeks |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|--|------------|--|--|---------|-----------------------------|--------------------------|
| SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE | Inhalation | respiratory system silicosis | All data are negative | Human | NOAEL Not available | occupational exposure |
| POLYETHYLENE GLYCOL | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 1.008 mg/l | 2 weeks |
| POLYETHYLENE GLYCOL | Ingestion | kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 5,640 mg/kg/day | 13 weeks |
| POLYETHYLENE GLYCOL | Ingestion | heart endocrine system hematopoietic system liver nervous system | All data are negative | Rat | NOAEL 5,640 mg/kg/day | 13 weeks |
| ALUMINUM OXIDE | Inhalation | pneumoconiosis pulmonary fibrosis | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | occupational exposure |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

3MTM ESPETM ScotchbondTM Universal Etchant 02/11/15

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility.

EPA Hazardous Waste Number (RCRA): D002 (Corrosive)

SECTION 14: Transport Information

For Transport Information, please visit <u>http://3M.com/Transportinfo</u> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

| Ingredient | C.A.S. No | <u>% by Wt</u> |
|----------------|------------------|----------------|
| ALUMINUM OXIDE | 1344-28-1 | < 2 |

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

Corrosive: Yes

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| Document Group: | 29-8286-6 | Version Number: | 2.00 |
|-----------------|-----------|------------------|----------|
| Issue Date: | 02/11/15 | Supercedes Date: | 06/06/12 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright,2014,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| Document Group: | 08-7419-8 | Version Number: | 12.00 |
|-----------------|-----------|------------------|----------|
| Issue Date: | 12/01/14 | Supercedes Date: | 12/27/11 |

SECTION 1: Identification

1.1. Product identifier

 $3M^{\mbox{\tiny TM}}$ ESPETM FILTEK TM P60 POSTERIOR RESTORATIVE PASTE

Product Identification Numbers

70-2010-2550-2, 70-2010-2551-0, 70-2010-2552-8, 70-2010-2580-9, 70-2010-2581-7, 70-2010-2582-5, 70-2010-2605-4, 70-2010-2606-2, 70-2010-2607-0, 70-2010-5197-9, 70-2010-5198-7, 70-2010-5199-5, 70-2010-8787-4, 70-2010-8788-2, 70-2010-8789-0

1.2. Recommended use and restrictions on use

Recommended use Dental Product, Restorative Restrictions on use For use only by dental professionals

| 1.3. Supplier's details | |
|-------------------------|---|
| MANUFACTURER: | 3M |
| DIVISION: | 3M ESPE Dental Products |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification Skin Sensitizer: Category 1B.

2.2. Label elements Signal word Warning

Symbols

3MTM ESPETM FILTEKTM P60 POSTERIOR RESTORATIVE PASTE 12/01/14

Exclamation mark |

Pictograms



Hazard Statements May cause an allergic skin reaction.

Precautionary Statements

Prevention:

Wear protective gloves. Contaminated work clothing must not be allowed out of the workplace.

Response:

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

None.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|-----------------------------------|-------------|------------------------|
| SILANE TREATED CERAMIC | 444758-98-9 | 75 - 85 Trade Secret * |
| BISPHENOL A POLYETHYLENE GLYCOL | 41637-38-1 | 1 - 10 Trade Secret * |
| DIETHER DIMETHACRYLATE (BISEMA6) | | |
| DIURETHANE DIMETHACRYLATE (UDMA) | 72869-86-4 | 1 - 10 Trade Secret * |
| BISPHENOL A DIGLYCIDYL ETHER | 1565-94-2 | 1 - 10 Trade Secret * |
| DIMETHACRYLATE (BISGMA) | | |
| TRIETHYLENE GLYCOL DIMETHACRYLATE | 109-16-0 | < 5 Trade Secret * |
| (TEGDMA) | | |
| ALUMINUM OXIDE | 1344-28-1 | < 5 Trade Secret * |
| BENZOTRIAZOL | 96478-09-0 | < 0.5 Trade Secret * |
| ETHYL 4-DIMETHYL AMINOBENZOATE | 10287-53-3 | < 0.5 Trade Secret * |
| (EDMAB) | | |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u> Carbon monoxide Carbon dioxide Condition During Combustion During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash

3MTM ESPETM FILTEKTM P60 POSTERIOR RESTORATIVE PASTE 12/01/14

thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|-------------------------------|------------|--------|----------------------------|----------------------------|
| Aluminum, insoluble compounds | 1344-28-1 | ACGIH | TWA(respirable fraction):1 | A4: Not class. as human |
| | | | mg/m3 | carcin |
| ALUMINUM OXIDE | 1344-28-1 | OSHA | TWA(as total dust):15 | |
| | | | mg/m3;TWA(respirable | |
| | | | fraction):5 mg/m3 | |
| ALUMINUM OXIDE | 1344-28-1 | CMRG | TWA:1 fiber/cc | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

Respiratory protection is not required.

SECTION 9: Physical and chemical properties

| 9.1. Information on basic phys | ical and chemical properties |
|--------------------------------|------------------------------|
|--------------------------------|------------------------------|

| General Physical Form: | |
|-------------------------|--|
| Specific Physical Form: | |
| Odor, Color, Grade: | |
| Odor threshold | |

Solid Paste Slight acrylate odor, various shades *No Data Available*

| рН | Not Applicable |
|---|----------------------------------|
| Melting point | No Data Available |
| Boiling Point | Not Applicable |
| Flash Point | No flash point |
| Evaporation rate | Not Applicable |
| Flammability (solid, gas) | Not Classified |
| Flammable Limits(LEL) | No Data Available |
| Flammable Limits(UEL) | No Data Available |
| Vapor Pressure | Not Applicable |
| Vapor Density | Not Applicable |
| Density | 2.1 g/cm3 |
| Specific Gravity | 2.1 [<i>Ref Std:</i> WATER=1] |
| Solubility in Water | Negligible |
| Solubility- non-water | No Data Available |
| Partition coefficient: n-octanol/ water | Not Applicable |
| Autoignition temperature | No Data Available |
| Decomposition temperature | No Data Available |
| Viscosity | Approximately 300,000 centipoise |
| Volatile Organic Compounds | No Data Available |
| Percent volatile | No Data Available |
| VOC Less H2O & Exempt Solvents | No Data Available |
| | |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions Hazardous polymerization will not occur.

10.4. Conditions to avoid None known.

10.5. Incompatible materials None known.

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

3MTM ESPETM FILTEKTM P60 POSTERIOR RESTORATIVE PASTE 12/01/14

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|---|-------------|-----------|---|
| Overall product | Ingestion | | No data available; calculated ATE 2,000 - 5,000 |
| | | | mg/kg |
| SILANE TREATED CERAMIC | Dermal | | LD50 estimated to be $> 5,000 \text{ mg/kg}$ |
| SILANE TREATED CERAMIC | Ingestion | | LD50 estimated to be 2,000 - 5,000 mg/kg |
| BISPHENOL A POLYETHYLENE GLYCOL DIETHER | Dermal | Professio | LD50 estimated to be $> 5,000 \text{ mg/kg}$ |
| DIMETHACRYLATE (BISEMA6) | | nal | |
| | | judgeme | |
| | | nt | |
| DIURETHANE DIMETHACRYLATE (UDMA) | Dermal | Professio | LD50 estimated to be $> 5,000 \text{ mg/kg}$ |
| | | nal | |
| | | judgeme | |
| | | nt | |
| BISPHENOL A POLYETHYLENE GLYCOL DIETHER | Ingestion | Rat | LD50 > 2,000 mg/kg |
| DIMETHACRYLATE (BISEMA6) | | | |
| DIURETHANE DIMETHACRYLATE (UDMA) | Ingestion | Rat | LD50 > 5,000 mg/kg |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE | Ingestion | | LD50 estimated to be 2,000 - 5,000 mg/kg |
| (BISGMA) | | | |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE | Dermal | Professio | LD50 estimated to be 2,000 - 5,000 mg/kg |
| (BISGMA) | | nal | |
| | | judgeme | |
| | | nt | |
| TRIETHYLENE GLYCOL DIMETHACRYLATE (TEGDMA) | Dermal | Professio | LD50 estimated to be $> 5,000 \text{ mg/kg}$ |
| | | nal | |
| | | judgeme | |
| | | nt | |
| TRIETHYLENE GLYCOL DIMETHACRYLATE (TEGDMA) | Ingestion | Rat | LD50 10,837 mg/kg |
| ALUMINUM OXIDE | Dermal | | LD50 estimated to be $> 5,000 \text{ mg/kg}$ |
| ALUMINUM OXIDE | Inhalation- | Rat | LC50 > 2.3 mg/l |
| | Dust/Mist | | |

3MTM ESPETM FILTEKTM P60 POSTERIOR RESTORATIVE PASTE 12/01/14

| | (4 hours) | | |
|--|-----------|-----|---------------------------------------|
| ALUMINUM OXIDE | Ingestion | Rat | LD50 > 5,000 mg/kg |
| ETHYL 4-DIMETHYL AMINOBENZOATE (EDMAB) | Dermal | Rat | LD50 > 2,000 mg/kg |
| ETHYL 4-DIMETHYL AMINOBENZOATE (EDMAB) | Ingestion | Rat | LD50 > 2,000 mg/kg |
| | | | · · · · · · · · · · · · · · · · · · · |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|-----------|---------------------------|
| SILANE TREATED CERAMIC | similar | No significant irritation |
| | compoun | |
| | ds | |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) | Not | Minimal irritation |
| | available | |
| TRIETHYLENE GLYCOL DIMETHACRYLATE (TEGDMA) | Guinea | Mild irritant |
| | pig | |
| ALUMINUM OXIDE | Rabbit | No significant irritation |
| ETHYL 4-DIMETHYL AMINOBENZOATE (EDMAB) | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|--|-----------|---------------------------|
| SILANE TREATED CERAMIC | similar | Mild irritant |
| | compoun | |
| | ds | |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) | Not | Moderate irritant |
| | available | |
| TRIETHYLENE GLYCOL DIMETHACRYLATE (TEGDMA) | Professio | Moderate irritant |
| | nal | |
| | judgeme | |
| | nt | |
| ALUMINUM OXIDE | Rabbit | No significant irritation |
| ETHYL 4-DIMETHYL AMINOBENZOATE (EDMAB) | Rabbit | Mild irritant |

Skin Sensitization

| Name | Species | Value |
|--|---------|--|
| SILANE TREATED CERAMIC | similar | Some positive data exist, but the data are not |
| | compoun | sufficient for classification |
| | ds | |
| BISPHENOL A POLYETHYLENE GLYCOL DIETHER | Guinea | Not sensitizing |
| DIMETHACRYLATE (BISEMA6) | pig | |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) | Guinea | Sensitizing |
| | pig | |
| TRIETHYLENE GLYCOL DIMETHACRYLATE (TEGDMA) | Human | Sensitizing |
| | and | |
| | animal | |

Respiratory Sensitization

| Name | Species | Value |
|------|---------|-------|
| | | |

Germ Cell Mutagenicity

| Name | Route | Value |
|--|----------|--|
| BISPHENOL A POLYETHYLENE GLYCOL DIETHER | In Vitro | Not mutagenic |
| DIMETHACRYLATE (BISEMA6) | | |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) | In Vitro | Some positive data exist, but the data are not |
| | | sufficient for classification |
| TRIETHYLENE GLYCOL DIMETHACRYLATE (TEGDMA) | In Vitro | Some positive data exist, but the data are not |
| | | sufficient for classification |
| ALUMINUM OXIDE | In Vitro | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|--|------------|---------|--|
| SILANE TREATED CERAMIC | Inhalation | similar | Some positive data exist, but the data are not |
| | | compou | sufficient for classification |
| | | nds | |
| TRIETHYLENE GLYCOL DIMETHACRYLATE (TEGDMA) | Dermal | Mouse | Not carcinogenic |

3MTM ESPETM FILTEKTM P60 POSTERIOR RESTORATIVE PASTE 12/01/14

| ALUMINUM OXIDE | Inhalation | Rat | Not carcinogenic |
|----------------|------------|-----|------------------|

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|---|-----------|----------------------------------|---------|------------------------|------------------------------------|
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) | Ingestion | Not toxic to female reproduction | Mouse | NOAEL 0.8 mg/kg/day | premating & during gestation |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) | Ingestion | Not toxic to male reproduction | Mouse | NOAEL 0.8 mg/kg/day | premating & during gestation |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) | Ingestion | Not toxic to development | Mouse | NOAEL 0.8 mg/kg/day | premating & during gestation |
| TRIETHYLENE GLYCOL DIMETHACRYLATE (TEGDMA) | Ingestion | Not toxic to female reproduction | Mouse | NOAEL 1 mg/kg/day | 1 generation |
| TRIETHYLENE GLYCOL DIMETHACRYLATE (TEGDMA) | Ingestion | Not toxic to male reproduction | Mouse | NOAEL 1 mg/kg/day | 1 generation |
| TRIETHYLENE GLYCOL DIMETHACRYLATE (TEGDMA) | Ingestion | Not toxic to development | Mouse | NOAEL 1 mg/kg/day | 1 generation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name Route Target Organ(s) Value Species Test | Result Exposure Duration |
|---|-----------------------------|
|---|-----------------------------|

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---|------------|--|--|--------------------------|------------------------|------------------------------------|
| SILANE TREATED CERAMIC | Inhalation | pulmonary fibrosis | Some positive data exist, but the data are not sufficient for classification | similar compoun ds | NOAEL Not available | |
| BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA) | Ingestion | endocrine system liver nervous system kidney and/or bladder | All data are negative | Mouse | NOAEL 0.8 mg/kg/day | premating & during gestation |
| TRIETHYLENE GLYCOL DIMETHACRYLATE (TEGDMA) | Dermal | kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Mouse | NOAEL 833 mg/kg/day | 78 weeks |
| TRIETHYLENE GLYCOL DIMETHACRYLATE (TEGDMA) | Dermal | blood | All data are negative | Mouse | NOAEL 833 mg/kg/day | 78 weeks |
| ALUMINUM OXIDE | Inhalation | pneumoconiosis pulmonary fibrosis | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | occupational exposure |

Aspiration Hazard

Name

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

Value

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material

3MTM ESPETM FILTEKTM P60 POSTERIOR RESTORATIVE PASTE 12/01/14

and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

| Ingredient | C.A.S. No | <u>% by Wt</u> |
|--------------------------------|-----------|----------------|
| ALUMINUM OXIDE (ALUMINUM OXIDE | 1344-28-1 | < 5 |
| (FIBROUS FORMS ONLY)) | | |
| ALUMINUM OXIDE | 1344-28-1 | < 5 |

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| Document Group: | 08-7419-8 | Version Number: | 12.00 |
|-----------------|-----------|------------------|----------|
| Issue Date: | 12/01/14 | Supercedes Date: | 12/27/11 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com