

SAFETY DATA SHEET

Silane Primer

Section 1. Identification

GHS product identifier

: Silane Primer

Other means of identification

: Not available.

Product type

: Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Dental product: Dental Restoration

Area of application: Professional applications.

Manufacturer : Kerr Corporation

1717 West Collins Avenue Orange, CA 92867-5422

Telephone no.: 1-800-KERR-123

e-mail address of person responsible for this SDS

: edwin.varela@kavokerrgroup.com

Emergency telephone number (with hours of

operation)

: CHEMTREC® (24 hours) U.S.: 1-800-424-9300 International: +1-703-527-3887

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Health effects are based on the uncured material.

Classification of the substance or mixture

: FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2A

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract

irritation and Narcotic effects) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 10.5%

GHS label elements

Hazard pictograms







Signal word

Danger

Hazard statements

Highly flammable liquid and vapor.
 Causes serious eye irritation.
 May cause respiratory irritation.
 May cause drowsiness and dizziness.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Date of issue/Date of revision : 03/26/2015 Date of previous issue : No previous validation Version : 1 1/12

Section 2. Hazards identification

Prevention

: Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Wash hands thoroughly after handling.

Response

: Get medical attention if you feel unwell. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage Disposal

- : Store locked up. Store in a well-ventilated place. Keep cool.
- : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements

: Avoid contact with skin and clothing. Wash thoroughly after handling.

Hazards not otherwise classified

: Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

Substance/mixture
Other means of

identification

: Not available.

CAS number/other identifiers

CAS number : Not applicable. **Product code** : Not available.

Ingredient name	Other names	%	CAS number
ethanol	ethanol	60-100	64-17-5
Poly(oxy-1,2-ethanediyl), α,α' -[(1-methylethylidene)di-4,1-phenylene]bis[ω -[(2-methyl-1-oxo-2-propen-1-yl)oxy]-	Not available.	1-5	41637-38-1
2,2'-ethylenedioxydiethyl dimethacrylate	2,2'-ethylenedioxydiethyl dimethacrylate	1-5	109-16-0
3-trimethoxysilylpropyl methacrylate	3-trimethoxysilylpropyl methacrylate	1-5	2530-85-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: No special measures are required. In case of contact with eyes, rinse immediately with plenty of water. Get medical attention if symptoms occur.

Inhalation

: No special measures required. If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Skin contact

: No special measures required. In case of contact, immediately flush skin with plenty of water. Get medical attention if symptoms occur.

Date of issue/Date of revision : 03/26/2015 Date of previous issue : No previous validation Version : 1 2/12

Section 4. First aid measures

Ingestion

: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Get medical attention if adverse health effects persist or are severe.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness and

dizziness. May cause respiratory irritation.

Skin contact: Defatting to the skin. May cause skin dryness and irritation.

Ingestion : Can cause central nervous system (CNS) depression. Irritating to mouth, throat and

stomach.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness

Skin contact: Adverse symptoms may include the following:

irritation dryness cracking

Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : In case of major fire and large quantities: No action shall be taken involving any

personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing

media

: Do not use water jet.

Date of issue/Date of revision : 03/26/2015 Date of previous issue : No previous validation Version : 1 3/12

Section 5. Fire-fighting measures

Specific hazards arising from the chemical

: Highly flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide metal oxide/oxides

Special protective actions for fire-fighters

: In case of major fire and large quantities: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: Low release. For professional use only. Handling of product in very small amounts or in situations where release is highly unlikely

For emergency responders: Low release. See also the information in "For non-emergency personnel".

Environmental precautions

: Low release. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Small Quantity. For professional use only. Absorb with an inert material and place in an appropriate waste disposal container.

Large spill

Small Quantity. For professional use only. Absorb with an inert material and place in an appropriate waste disposal container.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: No special measures are required for small quantities under normal and intended conditions of product use. For professional use only. Put on appropriate personal protective equipment (see Section 8). Handle with care and dispose in a safe manner.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Date of issue/Date of revision : 03/26/2015 Date of previous issue : No previous validation Version: 1 4/12

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits	
ethanol	ACGIH TLV (United States, 4/2014). STEL: 1000 ppm 15 minutes. OSHA PEL 1989 (United States, 3/1989). TWA: 1000 ppm 8 hours. TWA: 1900 mg/m³ 8 hours. NIOSH REL (United States, 10/2013). TWA: 1000 ppm 10 hours. TWA: 1900 mg/m³ 10 hours. OSHA PEL (United States, 2/2013). TWA: 1000 ppm 8 hours. TWA: 1900 mg/m³ 8 hours.	

Appropriate engineering controls

Environmental exposure controls

- : No special measures are required for small quantities under normal and intended conditions of product use.
- : No special measures are required for small quantities under normal and intended conditions of product use.

Individual protection measures

Hygiene measures

: No special measures are required for small quantities under normal and intended conditions of product use.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: No special measures are required for small quantities under normal and intended conditions of product use.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: No special measures are required for small quantities under normal and intended conditions of product use.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid. [Clear.]
Color : Colorless.
Odor : Alcohol-like.
Odor threshold : Not available.
pH : Not available.
Melting point : Not available.
Boiling point : 78.5°C (173.3°F)

Date of issue/Date of revision : 03/26/2015 Date of previous issue : No previous validation Version : 1 5/12

Section 9. Physical and chemical properties

Flash point : Closed cup: 13°C (55.4°F)

Vapor pressure : 5.3 kPa (40 mm Hg) [room temperature]

Vapor density : 1.59 [Air = 1]

Relative density : 0.85

Solubility : Insoluble in the following materials: cold water and hot water.

Solubility in water : Not available.

Partition coefficient: n- : Not available.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.Viscosity: Not available.

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Under normal conditions of storage and use, hazardous polymerization will not occur.

Conditions to avoid

: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.

Incompatible materials

: Reactive or incompatible with the following materials: oxidizing materials.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ethanol	LC50 Inhalation Vapor	Rat	124700 mg/m ³	4 hours
	LD50 Oral	Rat	7 g/kg	-
2,2'-ethylenedioxydiethyl dimethacrylate	LD50 Oral	Rat	10837 mg/kg	-
3-trimethoxysilylpropyl methacrylate	LD50 Oral	Rat	23504 mg/kg	-

Conclusion/Summary

 Based on the criteria of the protocol, this product is considered non-cytotoxic per ISO 10993-5.

Irritation/Corrosion

Date of issue/Date of revision : 03/26/2015 Date of previous issue : No previous validation Version : 1 6/12

Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
ethanol	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
				milligrams	
	Eyes - Moderate irritant	Rabbit	-	0.066666667	-
				minutes 100	
				milligrams	
	Eyes - Moderate irritant	Rabbit	-	100	-
				microliters	
	Eyes - Severe irritant	Rabbit	-	500	-
				milligrams	
	Skin - Mild irritant	Rabbit	-	400	-
				milligrams	
3-trimethoxysilylpropyl	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
methacrylate				milligrams	
	Skin - Mild irritant	Rabbit	-	24 hours 500	-
				milligrams	

Sensitization

3	Route of exposure	Species	Result
Silane Primer	skin	Guinea pig	Not sensitizing

Mutagenicity

Not available.

Conclusion/Summary

: Not mutagenic in Ames test.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
ethanol	-	1	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
ethanol	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Poly(oxy-1,2-ethanediyl), α,α' -[(1-methylethylidene)di-4,1-phenylene]bis[ω -[(2-methyl-1-oxo-2-propen-1-yl)oxy]-	Category 3	Not applicable.	Respiratory tract irritation
2,2'-ethylenedioxydiethyl dimethacrylate	Category 3	Not applicable.	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
ethanol	Category 2	Not determined	liver

Aspiration hazard

Not available.

Date of issue/Date of revision : 03/26/2015 Date of previous issue : No previous validation Version : 1 7/12

Section 11. Toxicological information

Information on the likely

routes of exposure

: Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects

Eye contact

: Causes serious eye irritation.

Inhalation

: Can cause central nervous system (CNS) depression. May cause drowsiness and

dizziness. May cause respiratory irritation.

Skin contact

: Defatting to the skin. May cause skin dryness and irritation.

Ingestion

: Can cause central nervous system (CNS) depression. Irritating to mouth, throat and

stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact

: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation

Adverse symptoms may include the following:

respiratory tract irritation

coughing

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness

Skin contact

: Adverse symptoms may include the following:

irritation dryness cracking

Ingestion

: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects

: Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : May cause damage to organs through prolonged or repeated exposure. Prolonged or

repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Date of issue/Date of revision : 03/26/2015 Date of previous issue : No previous validation Version : 1 8/12

Section 11. Toxicological information

Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
ethanol	Acute EC50 17.921 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia	48 hours
		franciscana - Larvae	
	Acute LC50 42000 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.375 ul/L Fresh water	Fish - Gambusia holbrooki -	12 weeks
		Larvae	

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
ethanol	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
ethanol	-0.35	-	low
Poly(oxy-1,2-ethanediyl), α,α' - [(1-methylethylidene)di-4,1- phenylene]bis[ω -[(2-methyl-1- oxo-2-propen-1-yl)oxy]-	3.43 to 5.62	2372	high
2,2'-ethylenedioxydiethyl dimethacrylate	1.88	-	low
3-trimethoxysilylpropyl methacrylate	2.1	-	low

Mobility in soil

Soil/water partition coefficient (K_{oc})

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Date of issue/Date of revision : 03/26/2015 Date of previous issue : No previous validation Version : 1 9/12

Section 14. Transport information

	DOT Classification	IMDG	IATA
UN number	UN1170	UN1170	UN1170
UN proper shipping name	Ethanol solutions	ETHANOL SOLUTION	Ethanol solution
Transport hazard class(es)	3	3	3
Packing group	II	II	II
Environmental hazards	No.	No.	No.
Additional information	Limited quantity Yes.	Emergency schedules (EmS) F-E, S-D	Passenger and Cargo Aircraft Quantity limitation: 5 L Packaging instructions: 353
	Packaging instruction Passenger aircraft Quantity limitation: 5 L Cargo aircraft Quantity limitation: 60 L Special provisions 24, IB2, T4, TP1	Special provisions 144	Cargo Aircraft Only Quantity limitation: 60 L Packaging instructions: 364 Limited Quantities - Passenger Aircraft Quantity limitation: 1 L Packaging instructions: Y341 Special provisions A3, A58, A180

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to Annex II of MARPOL

73/78 and the IBC Code

Section 15. Regulatory information

U.S. Federal regulations : TSCA 8(a) PAIR: mequinol; oxybenzone

United States inventory (TSCA 8b): All components are listed or exempted.

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)** : Not listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

: Not listed

Class II Substances DEA List I Chemicals

(Precursor Chemicals)

: Not listed

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Date of issue/Date of revision 10/12 : 03/26/2015 Date of previous issue : No previous validation Version: 1

Silane Primer

Section 15. Regulatory information

Composition/information on ingredients

			SARA 302 TPQ		SARA 304 RQ	
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
ethylene oxide	<0.00555	Yes.	1000	-	10	-

SARA 304 RQ : 200200.2 lbs / 90890.9 kg [28248 gal / 106930.5 L]

SARA 311/312

Classification : Fire hazard

Immediate (acute) health hazard Delayed (chronic) health hazard

Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
ethanol Poly(oxy-1,2-ethanediyl), α,α'-[(1- methylethylidene)di-4,1-phenylene]bis[ω-[(2-methyl-1-oxo-2-propen-1-yl)oxy]-	60-100 1-5	Yes. No.	No. No.	No. No.	Yes. Yes.	Yes. No.
2,2'-ethylenedioxydiethyl dimethacrylate 3-trimethoxysilylpropyl methacrylate	1-5 1-5	Yes. No.	No.	No.	Yes.	No.

SARA 313

Not applicable.

State regulations

Massachusetts : The following components are listed: ETHYL ALCOHOL

New York : None of the components are listed.

New Jersey : The following components are listed: ETHYL ALCOHOL; ALCOHOL

Pennsylvania: The following components are listed: DENATURED ALCOHOL

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Ingredient name	Cancer	•	level	Maximum acceptable dosage level
ethylene oxide	Yes.	Yes.	Yes.	Yes.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

Date of issue/Date of revision : 03/26/2015 Date of previous issue : No previous validation Version : 1 11/12

Section 16. Other information

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

History

Date of issue/Date of

revision

: 03/26/2015

Date of previous issue

: No previous validation

Version
Prepared by

: 1 : IHS

Key to abbreviations

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

References

: HCS (U.S.A.)- Hazard Communication Standard

International transport regulations

✓ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.