Complies with OSHA's Hazard Communication Standard 2012 and the Global Harmonized Standard (GHS).

Page 1 of 5

Section 1: Identification

Product Identification: Temporary Cement Remover Liquid Item Number: 00140

Manufactured by:

EPR Industries LLC. 4576 Crescent Boulevard Pennsauken, NJ 08109

Telephone: 1-856-488-1120

Emergency: Info-Trac 1-800-535-5053

Recommended use: Removal of temporary dental cements from instruments.

Section 2: Hazard(s)

Classification of the substance or mixture:

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS) Skin corrosion (Category 1A), H314 Serious eve damage (Category 1), H318

GHS Label elements, including precautionary statements

Pictogram Signal word Danger



Hazard statement(s)

H314 Causes severe skin burns and eye damage.

Precautionary statement(s)

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves / protective clothing / eye protection / face protection.

P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Complies with OSHA's Hazard Communication Standard 2012 and the Global Harmonized Standard (GHS).

Page 2 of 5

Product Identification: Temporary Cement Remover Liquid Item Number: 00140

Section 2 cont--

P310 Immediately call a POISON CENTER or doctor/ physician. P321 Specific treatment (see supplemental first aid instructions on this label) P363 Wash contaminated clothing before reuse.

Hazard Summary: Product contains sodium hydroxide, sodium metasilicate, and anionic surfactants. All precautions must be followed when using this product.

Section 3: Composition / information on Ingredients

Hazardous Ingredient(s)	CAS #	Exposure PEL, TLV, TWA	%
Sodium Hydroxide	[1310-73-2]	OSHA/ACGIH 2 mg/m3	< 3
Tetrasodium salt / EDTA	[64-02-08]	OSHA PEL: 2 MG/M3 / ACGIH TLV: C 2 MG/M3	< 5
Sodium metasilicate	[6834-92-0]	N/E	< 10

Section 4 : First-aid measures

EMERGENCY FIRST AID PROCEDURES

Eye Contact: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Cold water may be used. Do not use an eye ointment. **Seek immediate medical attention.**

Skin Contact: If the chemical got onto the clothed portion of the body, remove the contaminated clothes as quickly as possible, protecting your own hands and body. Place the victim under a deluge shower. If the chemical got on the victim's exposed skin, such as the hands : Gently and thoroughly wash the contaminated skin with running water and non-abrasive soap. Be particularly careful to clean folds, crevices, creases and groin. Cold water may be used. If irritation persists, seek medical attention. Wash contaminated clothing before reusing.

Serious Skin Contact: Wash with a disinfectant soap. Seek immediate medical attention.

Inhalation: Allow the victim to rest in a well ventilated area. Seek immediate medical attention.

Serious Inhalation: Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. WARNING: It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. **Seek immediate medical attention.**

Ingestion: Do not induce vomiting. Give large quantities of water or milk. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. **Seek immediate medical attention.**

Section 5 : Fire-fighting measures

Flash Point : Not flammable	Flammable limits : N/A	LEL : N/A	UEL : N/A
Extinguishing media: Not flam	mable.	Unusual fire and explosion hazards: None	

Special Fire Fighting Procedure: Product not flammable. No special requirements.

Complies with OSHA's Hazard Communication Standard 2012 and the Global Harmonized Standard (GHS).

Page 3 of 5

Product Identification: Temporary Cement Remover Liquid Item Number: 00140

Section 6: Accidental release measures

Personal precautions: Use personal protection per Section 8.

Small Spill: Use appropriate absorbent material to soak up spill. Put the solid waste in a convenient waste disposal container. If necessary: Neutralize the residue with a dilute solution of sodium carbonate.

Large Spill: Stop leak if without risk. Do not touch spilled material. Use water spray to reduce vapors. Prevent entry into sewers, basements or confined areas; dike if needed. Use appropriate absorbent material to soak up spill. Call for assistance on disposal. Neutralize the waste material with a dilute solution of sodium carbonate.

Section 7: Handling and storage

Keep container dry. Do not ingest. Do not inhale vapors. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes Handling: Use in well ventilated areas. Avoid contact with eyes.

Advice on protection against fire and explosion: Product is not flammable.

Storage: Store in well ventilated areas at ambient temp.

Advice on common storage: Do not store next to strong reducing agents, halogens or peroxides.

Section 8: Exposure control / personal protection

Engineering Measures: Provide normal room ventilation or local exhaust if necessary.

Personal Precautions: Always use protective clothing as specified below.

Eye Protection: Use safety goggles or approved safety glasses.

Hand Protection: Use protective gloves and discard after contact with product. Latex gloves are not a chemical barrier.

Skin and body protection: Pants, long sleeves, clinical jacket, apron.

Respiratory protection: Use clinical face mask when using Temporary Cement Remover as directed as long as adequate room ventilation is present. Avoid direct inhalation of vapors. Use NIOSH approved respirator if using this product in a confined space without adequate ventilation.

Hygiene measures: Wash hands after using. **Emergency eyewash station must be available.** Launder contaminated clothing.

Exposure Guidelines: None determined.

Section 9: Physical chemical properties

Boiling Point : Approx. 10	0 C Specific Gravity : > 1.10 @ 2	0C Vapor Pressure: (mm Hg) ND
Melting Point : N/A	Evaporation Rate : (n-butyl = 1)	ND Vapor Density : (Air = 1) 1.105 @ 15 C
Solubility in Water : Comp	lete pH: > 12	

Appearance and Odor: Clear, colorless liquid with irritating odor.

Complies with OSHA's Hazard Communication Standard 2012 and the Global Harmonized Standard (GHS).

Page 4 of 5

Product Identification: Temporary Cement Remover Liquid

Item Number: 00140

Section 10: Stability and reactivity

Materials to avoid: Avoid contact with strong oxidizing agents, strong acids, halogens, peroxides.

Hazardous decomposition products: Combustion may produce carbon monoxide, carbon dioxide, and nitrogen oxides.

Hazardous reactions: Will evolve gases if mixed with strong oxidizing agents and acids.

Do not mix with other chemicals.

Section 11: Toxicological information

Acute oral toxicity: Sodium Hydroxide = LD₅₀ 1350 mg/kg (rat)

 $EDTA = LD_{50}$ > between 630-1280 mg/kg (rat)

Not listed as a carcinogen by OSHA, IARC, AGCIH, or NTP.

Section 12: Ecological information

No data available.

Section 13: Disposal consideration

Waste/Disposal Information: Observe all Federal, State, and Local Environmental Regulations when disposing of this product.

Use and or alterations to this product such as mixing with other materials/chemicals may significantly change the characteristics of the material and alter product hazard classifications and the proper disposal method.

Section 14 : Transport information

Product is classified as a Hazardous Material:

DOT Classification: CLASS 8: Corrosive Solution

Identification: Sodium Hydroxide Solution:

UN1824

PG: II

Limited Quantity Exception for shipping : 173.154 Exception for Class 8 (corrosive materials) subpart b (2).

Section 15 : Regulatory information

SARA 302 Components:

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.



Complies with OSHA's Hazard Communication Standard 2012 and the Global Harmonized Standard (GHS).

Page 5 of 5

Product Identification: Temporary Cement Remover Liquid Item Number: 00140

Section 15 cont--

SARA 313 Components:

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards: Acute Health Hazard

Massachusetts Right To Know: No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know Components: Sodium Hydroxide CAS-No.1310-73-2 Revision Date 2007-03-01

New Jersey Right To Know Components: Sodium Hydroxide CAS-No.1310-73-2 Revision Date 2007-03-01

California Prop. 65 Components:

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Section 16 : Other information

Date prepared: February 2015 Revision: 1.00A

Information contained herein is furnished without warranties of any kind. Users should consider these data only as supplements to other information obtained by them and must make independent determinations of completeness and suitability of information from all sources to ensure proper disposal and use of materials for the safety and health of both employees and customers.