

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



Section I

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

IDENTITY (As used on Label and List) ABRASIVE DISCS, ET AL, GARNET, CUTTLE, SAND, EMERY, ADALOX, WATERPROOF, MOORE-FLEX

Manufacturer's Name
E. C. MOORE COMPANY INC.
Address (Number, Street, City, State, and ZIP Code)
13325 LEONARD STREET
DEARBORN, MI 48126

Emergency Telephone Number
(313) 581 7878
Telephone Number for Information
SAME
Date Prepared
Signature of Preparer (optional)

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
GARNET/GARNET	15MG/M3	10MG/M3	N	60
ALUMINUM OXIDE/CUTTLE	15MG/M3	10MG/M3	N	60
ALUMINUM OXIDE/SAND	15MG/M3	10MG/M3	N	60
SILICON CARBIDE/EMERY	15MG/M3	10MG/M3	N	60
ALUMINUM OXIDE/ADALOX	15MG/M3	10MG/M3	N	60
SILICON CARBIDE/WATERPROOF	15MG/M3	10MG/M3	N	60
BACKING CLOTH, MYLAR, PAPER	N/A	N/A	N	30
BINDER SYSTEM MIXTURE	N/A	N/A	N	10

Section III — Physical/Chemical Characteristics

Boiling Point	N/A	Specific Gravity (H ₂ O = 1)	N/A
Vapor Pressure (mm Hg.)	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water	N/A		
Appearance and Odor	COATED ABRASIVE PRODUCT		

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used)	NA	Flammable Limits	LEL N/A	UEL N/A
Extinguishing Media	CARBON DIOXIDE, FOAM, WATER			
Special Fire Fighting Procedures	BACKINGS AND RESIN BINDER WILL BURN OR DECOMPOSE, USE RESPIRATORY PROTECTION			
Unusual Fire and Explosion Hazards	N/A			

